

Plotting with GP

You can also make simple plots with GP, such as

```
? plot(t=0,Pi*2,[sin(t*17)*13,cos(t*52)],1)
%18 = [-12.99999286243945384, 12.99999286243945384, -0.999997803828127196
?
```

The final “1” indicates that this is plotted as a two-dimensional parametric function, i.e., the x coordinate is $x = \sin(17t)$, and the y coordinate is $y = \cos(52t)$.



Programming with GP

You can program inside of the gp shell. The basic control structures are

```
while(CONDITION, CODE)
```

```
if(CONDITION, THEN-CODE, ELSE-CODE)
```

```
for(VAR=A, B, CODE)
```

```
forstep(VAR=A, B, STEP, CODE)
```



Examples

```
? for(i=2,10,print(i*i%(i+10)))
4
9
2
10
4
15
10
5
0
```



Examples

```
? forstep(i=1,6,0.5,print(i))  
1  
1.5000000000000000000000000000000  
2.0000000000000000000000000000000  
2.5000000000000000000000000000000  
3.0000000000000000000000000000000  
3.5000000000000000000000000000000  
4.0000000000000000000000000000000  
4.5000000000000000000000000000000  
5.0000000000000000000000000000000  
5.5000000000000000000000000000000  
6.0000000000000000000000000000000  
?
```



Examples

```
? x = 0
%1 = 0
? while(x < 10, x = x+1; print(x))
1
2
3
4
5
6
7
8
9
10
?
```



Examples

```
? x = 10
%1 = 10
? while(x > 0, if(x % 2 == 0, x = x / 2 , x = x + 7); print(x))
5
12
6
3
10
5
12
[ ... ]
```



Defining functions

Function definition syntax:

```
NAME( [ARG1, [ARG2, [...]]] ) = local([ARG1, [ARG2, [...]]]) ; CODE
```

```
NAME( [ARG1, [ARG2, [...]]] ) =
{
  local([ARG1, [ARG2, [...]]]) ; CODE
}
```



Examples

```
/* long form */
? first_prime_div(x) =
{
  forprime(p=2,x,if(x % p == 0, return(p)))
}
? first_prime_div(35)
%19 = 5
?

/* short form */
? first_prime_div2(x) = forprime(p=2,x,if(x % p == 0, return(p)))
? first_prime_div2(161)
%20 = 7
```

